

THIN-CLAD CALCIUM SILICATE BRICK,
 MVIS™ THIN BRICK MORTAR -
 POLYMER FORTIFIED,
 PROGUARD DP® INSULATED CONCRETE
 BOARD PANEL - DOUBLE DRAINAGE
 PLANE (THICKNESS DEPENDENT ON
 REQUIRED R-VALUE),
 MVIS™ AIR & WATER BARRIER or
 WATERARMOR® AWB,
 EXTERIOR SHEATHING,
 STEEL STUD WALL,
 VAPOR BARRIER (LOCATION
 DEPENDENT ON CLIMATE ZONE),
 GYPSUM WALLBOARD

ARCHITECT NOTE:

- DETAIL FOR SUPPORTED PROGUARD DP® - DOUBLE DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT PROGUARD DP® SCREW SPACING USING NTA REPORT TRIG030116-28.

INSULATION CHAMFERED AT TOP AND
 BOTTOM OF PANEL EDGES TO ALLOW
 FOR CONTINUOUS DRAINAGE

OVERLAP AIR / MOISTURE BARRIER
 OVER FLASHING MEMBRANE

1'-0" x 8'-0" PROGUARD DP® BASE WEEP
 PANEL - DOUBLE DRAINAGE PLANE AT
 ALL FLASHING LOCATIONS

FLASHING MEMBRANE ADHERED
 MIN. 4" UP SUBSTRATE

ATTACH PROGUARD DP® PANELS
 WITH SILVER C APPROVED SCREWS
 THROUGH TO STUDS (TYPICAL)

TAPE JOINT WITH ALKALI-RESISTANT
 MESH TAPE AND MUD JOINT WITH
 MVIS™ THIN BRICK MORTAR

MVIS™ POINTING MORTAR

COMPRESSIBLE BACKER ROD
 AND SILICONE SEALANT w/
 WEEP HOLES @ 8" o.c.

PREFINISHED METAL
 FLASHING w/ DRIP EDGE

ADAI® LIMESTONE BASE COURSE

COMPRESSIBLE BACKER ROD
 AND SILICONE SEALANT
 PREMOLDED EXPANSION JOINT FILLER
 2% SLOPE MIN.

BUILDING PAPER

AIR / VAPOR BARRIER



ARRISCRAFT · CADD

TITLE: FOUNDATION WALL / BURIED
 BRICK UNIT (ADAI® LIMESTONE
 BASE COURSE) WITH PAVING

DETAIL No:

SSETB - DP2S

U007

DATE DRAWN:
 02 Mar 2022

SCALE:
 3"=1'-0"

DRAWN BY:
 TRI