

NOTE: REFER TO

WINDOW SILL: SSETB-DP2SU026-28

WINDOW HEAD: SSETB-DP2SU032

COMPRESSIBLE BACKER ROD AND
SILICONE SEALANT AROUND FRAME

SPRAY APPLIED FOAM INSULATING
AIR SEAL AROUND FRAME

WATERPROOFING
TRANSITION MATERIAL

PREMANUFACTURED
THERMALLY BROKEN
ALUMINUM WINDOW ASSEMBLY

ATTACH PROGUARD DP® PANELS
WITH SILVER C APPROVED SCREWS
THROUGH TO STUDS (TYPICAL)

MVIS™ POINTING MORTAR

TAPE JOINT WITH ALKALI-RESISTANT
MESH TAPE AND MUD JOINT WITH
MVIS™ THIN BRICK MORTAR

PREFINISHED ALUMINUM or CALCIUM
SILICATE SILL c/w END DAMS

PROGUARD DP® PANEL INSULATION
CUT OUT OF RETURN PANEL TO
INTERFACE WITH FRONT-FACING
PROGUARD DP® PANEL

ARCHITECT NOTE:

- DETAIL FOR SUPPORTED
PROGUARD DP® - DOUBLE
DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT
PROGUARD DP® SCREW SPACING
USING NTA REPORT TRIG030116-28.

THIN-CLAD CALCIUM SILICATE BRICK,
MVIS™ THIN BRICK MORTAR -
POLYMER FORTIFIED,
PROGUARD DP® INSULATED CONCRETE BOARD
PANEL - DOUBLE DRAINAGE PLANE (THICKNESS
DEPENDENT ON REQUIRED R-VALUE),
MVIS™ AIR & WATER BARRIER or
WATERARMOR® AWB,
EXTERIOR SHEATHING,
STEEL STUD WALL,
VAPOR BARRIER (LOCATION
DEPENDENT ON CLIMATE ZONE),
GYPSUM WALLBOARD



ARRISCRAFT · CADD

TITLE: WINDOW JAMB - PROGUARD
DP® PANELS w/ INSULATION
CUT OUT (PLAN VIEW)

DETAIL No:

SSETB - DP2S

U044

DATE DRAWN:

02 Mar 2022

SCALE:

1-1/2"=1'-0"

DRAWN BY:

TRI