

## NOTE: REFER TO

DOOR THRESHOLD: SSETB-DP2SU052

DOOR HEAD: SSETB-DP2SU062

COMPRESSIBLE BACKER ROD AND  
SILICONE SEALANT AROUND FRAME

SPRAY APPLIED FOAM INSULATING  
AIR SEAL AROUND FRAME

WATERPROOFING  
TRANSITION MATERIAL

PREMANUFACTURED THERMALLY  
BROKEN ALUMINUM DOOR ASSEMBLY

ATTACH PROGUARD DP® PANELS  
WITH SILVER C APPROVED SCREWS  
THROUGH TO STUDS (TYPICAL)

MVIS™ POINTING MORTAR

TAPE JOINT WITH ALKALI-RESISTANT  
MESH TAPE AND MUD JOINT WITH  
MVIS™ THIN BRICK MORTAR

SLOPED THRESHOLD SILL

1/4" CONCRETE BOARD ATTACHED  
TO SHEATHING AND PROGUARD DP®  
PANELS WITH POLYURETHANE  
ADHESIVE AT JAMB RETURN

## ARCHITECT NOTE:

- DETAIL FOR SUPPORTED  
PROGUARD DP® - DOUBLE  
DRAINAGE PLANE PANELS.
- ENGINEER OF RECORD TO SELECT  
PROGUARD DP® SCREW SPACING  
USING NTA REPORT TRIG030116-28.

THIN-CLAD CALCIUM SILICATE BRICK,  
MVIS™ THIN BRICK MORTAR -  
POLYMER FORTIFIED,  
PROGUARD DP® INSULATED CONCRETE BOARD  
PANEL - DOUBLE DRAINAGE PLANE (THICKNESS  
DEPENDENT ON REQUIRED R-VALUE),  
MVIS™ AIR & WATER BARRIER or  
WATERARMOR® AWB,  
EXTERIOR SHEATHING,  
STEEL STUD WALL,  
VAPOR BARRIER (LOCATION  
DEPENDENT ON CLIMATE ZONE),  
GYPSUM WALLBOARD



**ARRISCRAFT · CADD**

TITLE:  
**DOOR JAMB - DEEP RECESSED  
DOOR (PLAN VIEW)**

DETAIL No:

SSETB - DP2S

**U072**

DATE DRAWN:

02 Mar 2022

SCALE:

1-1/2"=1'-0"

DRAWN BY:

TRI